

DeviceMaster[®] RTS

2-Port 1E



Part Number
99480-0

Control's DeviceMaster RTS line offers enhanced performance, features and reliability with the introduction of the DeviceMaster RTS 2-Port 1E.

DeviceMaster 1E features convenient DIN Rail enclosure designs, wide input voltage ranges, and screw terminal connectors. This product presents a seamless solution for integrating serial and network communication for applications in traffic and transportation, industrial automation, material handling, or any project that requires serial-to-Ethernet communication with DIN Rail-based equipment installations.

This serial device server can be used to network enable two serial devices on any Ethernet network. DeviceMaster RTS products supply screw terminal connections for each serial port and support RS-232, RS-422, and RS-485 serial communications at standard baud rates from 300 bps to 230 Kbps. The DeviceMaster RTS 2-Port 1E offers a single RJ45 jack with a 10/100 Ethernet connection to the network.

The product will accept power in the range of 5-30 volts DC through screw terminal connections. A 90-264VAC power supply is also available.

Highlights

- Proven DeviceMaster Performance
- Serial Communications Speeds up to 230Kbps Per Port
- RS-232, RS-422, RS-485 Software Selectable Interfaces
- Microsoft Certified Drivers for Windows Vista, Windows XP, and Windows Server 2003
- Convenient DIN Rail Design
- Screw Terminal Connections
- Wide Input Power Range
- RoHS Compliant

Specifications

HARDWARE

- Bus Interface Specification 10/100 Base-T
- Memory
 - SDRAM 8 MB
 - Flash 4 MB
- Enclosure UL94-V0 Plastic
- Installation Method Din Rail (35mm)
- LED Indicators
 - Ethernet activity, ethernet link and status
- Enclosure Dimensions 4.37" x 3.9" x .89"
- Product Weight 4.6 oz

ELECTRICAL SPECIFICATIONS

- DC Input Voltage 5-30 V
- Current Consumption
 - +24 VDC 60 mA
- Power Consumption (max) 1.5 W
- ESD Surge Protection (min) 25KV

ENVIRONMENTAL SPECIFICATIONS

- Operating Temperature -37 to 74°C
- Storage Temperature -40 to 85°C
- Operating Humidity
 - Non-condensing 5% to 95%
- Altitude 0 to 10000 Feet
- Heat Output 5.0 BTU/Hr
- MTBF 58.57 Years

SERIAL COMMUNICATIONS

- Connector Type
 - (2) Screw Terminal Blocks
- Interface Standard RS-232, RS-422, RS-485 Half-Duplex, RS-485 Full-Duplex
- Baud Rates 300 to 230.4Kbps
- Transmit Buffer 256 Bytes
- Receive Buffer 1024 Bytes
- Data Bits 7 or 8
- Parity odd, even or none
- Stop Bits 1 or 2
- Flow Control
 - Hardware, Software, None

ETHERNET SPECIFICATIONS

- Network Protocols
 - ARP, BOOTP, DHCP, HTTP, ICMP, Ping, RARP, RFC 1006 (ISO over TCP), RFC 2217, SNMP (MIB-II), TCP/IP, Telnet, TFTP, and UDP socket services
- Connector Type
 - (1) RJ45F
 - Auto MDI/MDI-X

EXPORT INFORMATION

- Packaged Shipping Weight 0.91 lbs
- Package Dimensions 9.25" x 2.5" x 7.25"
- UPC Code 7-56727-99480-0
- Country of Origin USA
- ECCN 5A991
- Schedule B Number 8471.80.1000

DEVICE DRIVERS

- Linux
- Microsoft® Windows Server® 2003
- Microsoft® Windows Vista™
- Microsoft® Windows® 2000
- Microsoft® Windows® XP

REGULATORY APPROVAL MARKS

- RoHS 2002/95/EC
- CE
- FCC
- UL/cUL
- C-Tick

REGULATORY STANDARDS

- Emission:
 - CANADIAN EMC REQUIREMENTS
 - ICES-003
 - European Standard EN55022
 - FCC PART 15 SUBPART B
 - CLASS A LIMIT
 - AS/NZS CISPR 22
- Immunity:
 - European Standard EN55024
 - IEC 1000-4-2/EN61000-4-2: ESD
 - IEC 1000-4-3/EN61000-4-3: RF
 - IEC 1000-4-4/EN61000-4-4: Fast Transient
 - IEC 1000-4-5/EN61000-4-5: Surge
 - IEC 1000-4-6/EN61000-4-6: Conducted Disturbance
 - IEC 1000-4-8/EN61000-4-8: Magnetic Field
 - IEC 1000-4-11/EN61000-4-11: Dips and Voltage Variations
- Safety:
 - IEC 60950/EN60950
 - CSA C22.2 No. 60950/UL60950 Third Edition
 - European Standard: 2002/95/EC Directive (RoHS)
 - NEMA TS2 Compliant

FEATURES

- SNMP Support
- RoHS Compliant
- 2-Year Warranty

Ordering Information

99480-0 DeviceMaster RTS 2-Port 1E

Product Support & Service Information

Warranty Information

Comtrol offers a 30-day satisfaction guarantee and 2-year limited warranty on all DeviceMaster products.

Sales Support

+1.763.494.4100
sales@comtrol.com

Technical Support

+1.763.494.4100
www.comtrol.com/support

Email, FTP, and Web Support

info@comtrol.com
ftp.comtrol.com
www.comtrol.com

