



### SVFT-UPM-1 Outdoor Parapet Mount for SurveyorVFT Camera Dome System

- Designed specifically for parapet mounting of SurveyorVFT
- Allows convenient cabling for ease of installation
- Easy serviceability

The SVFT-UPM-1 parapet mount is a heavy-duty unit designed specifically for mounting SurveyorVFT Camera Dome Systems from the inside surface of a roof parapet or similar structure. The SVFT-UPM-1 has a maximum load rating of 40 pounds (18 kg) and provides a sturdy installation capable of withstanding extreme weather conditions.

The SVFT-UPM-1 allows the mounted equipment to be swiveled in toward the roof to provide access for convenient rooftop servicing or adjustment. All cabling is conveniently routed through the mount.

#### ASSOCIATED EQUIPMENT AND ACCESSORIES

**Model SurveyorVFT Camera Dome System:** A compact high-speed dome unit with an integral receiver, pan/tilt drive and camera/lens module. The SurveyorVFT system is modular and can be outfitted for indoor and outdoor use, with a variety of mounting accessories, and for various camera/lens module types. Refer to Product Specification V134.

## Technical Information

#### MECHANICAL

- Mounting Flange**  
**Thread:** 1-1/2 in. NPT-F pipe thread.  
**Size:** Height (H): 37.0 in. (940 mm).  
 Width (W): 27.0 in. (686 mm).  
 See Figure.  
**Weight:** 7.6 lb (3.4 kg).  
**Load Rating:** 40 lb (18 kg). Designed to support the SurveyorVFT Dome.  
**Minimum Height of Parapet:** 16 in. (406 mm).  
**Minimum Separation Between Brackets:** 12.0 in. (305 mm).  
**Construction:** Mount: aluminum.  
 Brackets: steel.  
 Hardware: stainless steel.  
**Finish:** White paint.  
**Shipping Dimensions:** (H x W x D): 2.5 x 38 x 30 in. (63.5 x 965 x 762 mm).  
**Shipping Weight:** 10 lb (4.5 kg).  
**Shipping Volume:** 1.65 ft<sup>3</sup> (0.05 m<sup>3</sup>).

#### ENVIRONMENTAL

- Storage Temperature:** -40 to 150° F (-40 to 65° C).  
**Storage Humidity:** 90% relative, noncondensing.

